

WC-SYSTEM FOR DRY-WALL CONSTRUCTION VICONNECT

PRODUCT INFORMATION

1 . POSITION



Model	922478
Collection	ViConnect
PROJECTS	 PLUS
Width	525 mm
Height	985 mm
Depth	135 mm
Weight	14,5 kg
description	<p>for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc., adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200mm, depth adjustment front edge of element: 135-205 mm</p> <p>incl. 2 wall mounts, incl. self-locking feet with adjustable base plates and fastening materials, 2 times M12 WC retaining bolts adjustable to 180/230mm with protection plugs and nuts, installation instructions, without flush plate</p> <p>tested in accordance with DIN EN 14055</p> <p>packaged in a box</p> <p>For combination with: for wall-mounted WC</p> <p>self-supporting powder-coated steel frame, fully pre-assembled, front/top operated, with small inspection opening</p> <p>concealed cistern insulated against condensation water, with dual flush (7.5-4.5 l / 4-2 l), factory setting 6/3 l, adjustable flush flow control for adaptation to rimless toilet bowls, filling valve Noise Class I, corner valve R1/2, drain bend clamp, 4 adjustment settings, PE toilet connecting bend DN 90 (Ø 90) with reducing sleeve DN 90 (Ø 90) / DN 100 (Ø 110) with protection plugs, complete WC connection set DN 90 (Ø 90) / 180 mm, protection box for access opening can be cut to size, flexible hose for filling valve, can be tightened by hand, certification marks for concealed cistern: Noise Class I</p> <p>for dry-wall construction, low</p>

Specification texts

ViConnect; Toilet installation system; Size: 525 x 985 x 135 mm; for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc., adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200mm, depth adjustment front edge of element: 135-205 mm; incl. 2 wall mounts, incl. self-locking feet with adjustable base plates and fastening materials, 2 times M12 WC retaining bolts adjustable to 180/230mm with protection plugs and nuts, installation instructions, without flush plate; tested in accordance with DIN EN 14055; packaged in a box; For combination with: for wall-mounted WC; self-supporting powder-coated steel frame, fully pre-assembled, front/top operated, with small inspection opening; concealed cistern insulated against condensation water, with dual flush (7.5-4.5 l / 4-2 l), factory setting 6/3 l, adjustable flush flow control for adaptation to rimless toilet bowls, filling valve Noise Class I, corner valve R1/2, drain bend clamp, 4 adjustment settings, PE toilet connecting bend DN 90 (Ø 90) with reducing sleeve DN 90 (Ø 90) / DN 100 (Ø 110) with protection plugs, complete WC connection set DN 90 (Ø 90) / 180 mm, protection box for access opening can be cut to size, flexible hose for filling valve, can be tightened by hand, certification marks for concealed cistern: Noise Class I; for dry-wall construction, low

COLOURS

92247800 4051202338039

TECHNICAL DRAWINGS

922478

