


SYSTEM FOR DRY-WALL CONSTRUCTION VICONNECT

PRODUCT INFORMATION

1 . POSITION



| | |
|--------------|--|
| Model | 922149 |
| Collection | ViConnect |
| PROJECTS |  PLUS |
| Width | 525 mm |
| Height | 1120 mm |
| Depth | 75 mm |
| Weight | 8 kg |
| description | for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc., adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200mm, adjustment range front to wall: 135-205mm (when mounted on wall brackets) with wall brackets, with protection cap for the flushing pipe, installation instructions, incl. self-locking feet with adjustable base plates and fastening materials individual packaging materials self-supporting powder-coated steel frame, fully pre-assembled suitable for all washbasins and handwashbasins, with multiply bonded laminated wood panel and scaling for the free positioning of drinking water pipe wall panels, with 2 x M10 bolts for fastening washbasin, including protection plugs and washbasin fastenings, with universal waste bend DN 50 (Ø 50) / DN 40 (Ø 40) incl. rubber collar for odour trap outlet connector DN 40 (Ø 40) / DN 32 (Ø 32), protection plugs and sound-absorbing clamp for dry-wall construction, standard height |



PROJECTS

Specification texts

ViConnect; Washbasin installation element; Size: 525 x 1120 x 75 mm; for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc., adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200mm, adjustment range front to wall: 135-205mm (when mounted on wall brackets); with wall brackets, with protection cap for the flushing pipe, installation instructions, incl. self-locking feet with adjustable base plates and fastening materials; individual packaging materials; self-supporting powder-coated steel frame, fully pre-assembled; suitable for all washbasins and handwashbasins, with multiply bonded laminated wood panel and scaling for the free positioning of drinking water pipe wall panels, with 2 x M10 bolts for fastening washbasin, including protection plugs and washbasin fastenings, with universal waste bend DN 50 (Ø 50) / DN 40 (Ø 40) incl. rubber collar for odour trap outlet connector DN 40 (Ø 40) / DN 32 (Ø 32), protection plugs and sound-absorbing clamp; for dry-wall construction, standard height

COLOURS

92214900 4051202497620

TECHNICAL DRAWINGS

922149

