SHOWER TRAYS (ACRYLIC, QUARYL) SQUARO INFINITY

PRODUCT INFORMATION

1. POSITION



Model	UDQ1070SQI2LV
Collection	Squaro Infinity
PROJECTS	DESIGN
Width	700 mm
Height	40 mm
Depth	15 mm
Length	1000 mm
Weight	21 kg
description	corner installation, left against the wall

Technical information:: Cut shower tray (side unprocessed)., Drainage capacity: 48 l/min, The installation height of the shower tray can be reduced by 30 mm if the Viega outlet fitting art. no. 634 100 is used. Please note: this outlet fitting does not conform to EN 274., All shower trays are classified as antislip class C (in accordance with DIN51097), Surface-mounted models can be fitted in corners on the left against the wall, in a niche or flush-fit with the floor., Quaryl shower trays can be cut to size on site according to the installation instructions; detailed video at pro.villeroy-boch.com/ squaroinfinity or QR code on this page.

Outlet cover in matching matt colour with chrome-plated strip., **The extra charge for cutting already in the total price!**

Not included in scope of delivery:: All shower trays are supplied without support/base., With cut shower trays, we recommend the use of a composite seal in accordance with ETAG 022 on the floor structure below the shower tray in order to prevent any moisture from penetrating the floor structure.

With cut shower trays, we recommend the use of a composite seal in accordance with ETAG 022 on the floor structure below the shower tray in order to prevent any moisture from penetrating the floor structure.

Diameter: 90 mm

<u>Villeroy & Boch</u> 1748

PROJECTS

Quaryl®

material

Specification texts

Squaro Infinity; Shower tray; Size: 1000 x 700 x 40 mm; Quaryl®; corner installation, left against the wall: Outlet cover in matching matt colour with chrome-plated strip., The extra charge for cutting already in the total price!; Not included in scope of delivery:: All shower trays are supplied without support/base., With cut shower trays, we recommend the use of a composite seal in accordance with ETAG 022 on the floor structure below the shower tray in order to prevent any moisture from penetrating the floor structure.; Diameter: 90 mm; With cut shower trays, we recommend the use of a composite seal in accordance with ETAG 022 on the floor structure below the shower tray in order to prevent any moisture from penetrating the floor structure.; Technical information:: Cut shower tray (side unprocessed)., Drainage capacity: 48 l/min, The installation height of the shower tray can be reduced by 30 mm if the Viega outlet fitting art. no. 634 100 is used. Please note: this outlet fitting does not conform to EN 274., All shower trays are classified as antislip class Ć (in accordance with DIN51097), **Surface-mounted** models can be fitted in corners on the left against the wall, in a niche or flush-fit with the floor., Quaryl shower trays can be cut to size on site according to the installation instructions; detailed video at pro.villeroy-boch.com/ squaroinfinity or QR code on this page.

COLOURS

Anthracite	UDQ1070SQI2LV-1S	4051202456320
Crème	UDQ1070SQI2LV-2S	4051202457532
Grey	UDQ1070SQI2LV-3S	4051202458744
Brown	UDQ1070SQI2LV-4S	4051202459956
Stone White	UDQ1070SQI2LV-RW	4051202851408



TECHNICAL DRAWINGS





TECHNICAL DRAWINGS

